

TEMPSTAR®

Heating and Cooling Products

Duct Free Split Air Conditioner
18,000 through 36,000 Btuh

FEATURES

Attractive design with modern appearance
Auto-Swing Air Movement
Washable return air filter cartridges
LCD wireless remote
Multi-speed blowers designed for quiet operation
High Efficiency copper tubes with aluminum fin coils

HWS SERIES INDOOR



PRELIMINARY SUBJECT TO CHANGE

Representative Photo Only - Individual Units may be different

SPECIFICATIONS - INDOOR UNIT

Model - INDOOR SECTION		HWSW18AWA	HWSW24AWA	HWSR36AWA
System Cooling Capacity Btuh		17,500	22,000	33,000
System Cooling Input Power Watts		1,920	2,520	3,666
Electrical Data	Input Voltage	220-1-50		
	Voltage Range	198 -242		
Indoor Unit	Noise Level dBA (High Speed)	40	45	45
	Motor Watts	31	56	89
	Motor Running Amps	0.15	0.25	0.45
	Motor Speeds	3	3	3
	Air Flow High Speed (cfm/cmh)	450 / 765	550 / 935	900 / 1530
Net	Height (mm)	313	313	325
	Width (mm)	1167	1167	1190
	Depth (mm)	175	175	215
	Weight (kg)	14.0	14.0	17.0
Shipping	Height (mm)	373	373	385
	Width (mm)	1227	1227	1255
	Depth (mm)	235	235	260
	Weight (kg)	17.0	17.0	20.5

SPECIFICATIONS - OUTDOOR UNIT

MODEL NUMBER		NAC018AWA	NAC024AWA	NAC036AWA
Electrical Data	Input Voltage	220-1-50		
	Voltage Range	198 -242		
	Rated Load Amps	9.9	12.4	15.9
	Locked Rotor Amps	55.0	73.0	94.0
	Unit Type	Vertical Discharge	Vertical Discharge	Vertical Discharge
	Compressor Type	Reciprocating	Reciprocating	Reciprocating
	Noise Level dBA	72	72	74
	Refrigerant Fittings	Sweat Valve		
	Liquid line size (inches)	3/8	3/8	3/8
	Suction line size (inches)	3/4	3/4	3/4
Net	Height (mm)	610	661	711
	Width (mm)	629	629	629
	Depth (mm)	673	673	673
	Weight (kg)	61.2	62.3	65.7
Shipping	Height (mm)	670	711	761
	Width (mm)	654	654	654
	Depth (mm)	700	700	700
	Weight (kg)	63.0	64.1	67.5

Note: Matching accessory required part number HWCK1236WA includes 220V contactor, orifice body and orifice pins



International Comfort Products
650 Heil Quaker Avenue
Lewisburg Tennessee 37091

421 21 9216 00
Jun-01